

## GETT® 66 KEYS TRACKBALL



GA-66F1-TB-USB-US (FRONT)



GA-66R1-TB-USB-US (REAR)

### SPECIAL FEATURES

- Water, dust and vandal resistant
- Etching and inking lettering
- Brushed surface
- Compatible with WINDOWS98/ME/2000/XP
- Can be cleaned with soapy water, disinfectant or other cleaning agents
- Designed for public, outdoor, industrial and other extreme surroundings

### SPECIFICATION

| Model No.              | GA-66R1-TB-USB-US         | GA-66R1-TB-USB-US-LED | GA-66F1-TB-USB-US | GA-66F1-TB-USB-US-LED |
|------------------------|---------------------------|-----------------------|-------------------|-----------------------|
| Mounting               | rear                      |                       | front (+3USD)     |                       |
| Backlight              | absent                    | present (+35USD)      | absent            | present (+35USD)      |
| Contact technology     | carbon on gold            |                       |                   |                       |
| Connectivity           | USB or PS/2               |                       |                   |                       |
| Number of keys         | 66 keys                   |                       |                   |                       |
| Key stroke travel      | 1.5mm                     |                       |                   |                       |
| Switching cycles       | approx. 1 mill. (per key) |                       |                   |                       |
| Protection level       | IP65                      |                       |                   |                       |
| Impact protection rate | IK07                      |                       |                   |                       |
| Housing colour         | stainless steel           |                       |                   |                       |
| Operating temperature  | -10°C ~ +45°C             |                       |                   |                       |
| Storage temperature    | -20°C ~ + 70°C            |                       |                   |                       |
| Relative humidity      | 30% to 95%                |                       |                   |                       |
| Atmospheric pressure   | 50kPa to 110kPa           |                       |                   |                       |
| Key actuation force    | 120g/1.18N                |                       |                   |                       |
| Power input            | +5V/DC, 10mA              |                       |                   |                       |
| Warranty               | 1 year                    |                       |                   |                       |
| Dimensions (mm)        | 392 x 110                 |                       | 400 x 124         |                       |
| Net Weight (kg)        | 1.6                       |                       | 1.5               |                       |
| Gross Weight (kg)      | 2.1                       |                       | 1.8               |                       |
| Certification          | EMC, FCC, CE              |                       |                   |                       |

Other layouts and configurations on request.