



# SUPER Touch Monitor



	7" Touch Monitor	10.1" Touch Monitor	10.4" Touch Monitor	15.1" Touch Monitor
Model Name	7"	10.1"	10.4"	15.1"
Dimension	37.9H x 225.3W x 166.8D mm	38.6H x 293.4W x 210.4D mm	38.6H x 296W x 250.4D mm	40.5H x 404.1W x 335D mm
Case Material	ABS front frame + housing	ABS front frame + housing	ABS front frame + housing	ABS front frame + housing
Weight	0.9 Kg	1.3 Kg	1.4 Kg	3.7 Kg
Mounting Spec.	VESA 75 / Wall Mount	VESA 75 / Wall Mount	VESA 75 / Wall Mount	VESA 75 / Wall Mount
Panel Frame Water Proof	IP65	IP65	IP65	IP65
Optional Accessory	Wall Mount Kit / Stand	Wall Mount Kit / Stand	Wall Mount Kit / Stand	Wall Mount Kit / Stand
Max Resolution	1024 x 600	1280 x 800	1024 x 768	1024 x 768
Color Support	116.2M / 262K colors	116.2M / 262K colors	116.2M / 262K colors	116.2M / 262K colors
Max Sync Rate (V x H)	60 Hz x 80 kHz	60 Hz x 80 kHz	60 Hz x 80 kHz	60 Hz x 80 kHz
Response Time	10 ms (Falling time) 15 ms (Raising time)	10 ms (Falling time) 20 ms (Raising time)	11 ms (Falling time) 14 ms (Raising time)	2.3 ms (Falling time) 5.7ms (Raising time)
Touch Screen	4 wires Resistive Touch screen	5 wires Resistive Touch screen	5 wires Resistive Touch screen	5 wires Resistive Touch screen
Image Aspect Ratio	16:9	16:9	4:3	4:3
Brightness	500	300	350	450
Contrast Ratio	800:1	1300:1	1200:1	800:1
H-View Angle	150°	160°	176°	160°
V-View Angle	145°	140°	176°	150°
Signal Interfaces	VGA / DVI, USB Touch	VGA / DVI, USB Touch	VGA / DVI, USB Touch	VGA / DVI, USB Touch
Voltage Required	DC9~36V	DC9~36V	DC9~36V	DC9~36V
Power Consumption Operational	0.57A max.	0.57A max.	0.6A max.	1.02A max.
Operating Temperature	-20°C ~ 60°C	-20°C ~ 60°C	-20°C ~ 60°C	-20°C ~ 60°C
Operation Humidity Range	5~90% RH @ 39°C, non-condensing	5~90% RH @ 39°C, non-condensing	5~90% RH @ 39°C, non-condensing	5~90% RH @ 39°C, non-condensing
Storage Temperature	-30°C~+80°C	-30°C~+80°C	-30°C~+80°C	-20°C~+65°C
Storage Humidity Range	5~90% RH @ 39°C, non-condensing			