

<b>Model No.</b>	<b>DK3100I-4F2FS</b>			
<b>Interface</b>	Fiber ports	Copper RJ45 ports		
	2	4		
<b>Ethernet</b>	4*10/100Base-TX RJ45 2*100Base-FX SFP			
<b>Standard</b>	IEEE 802.3 10Base-T Ethernet IEEE 802.3u Fast Ethernet IEEE 802.3x Full-Duplex Flow Control IEEE 802.3az Energy Efficient Ethernet			
<b>Dip Switch</b>	1. Port Isolation 2. Flow control 3. QoS(1-2 ports) 4. Broadcast storm restrain			
<b>LED Indicators</b>	P(Power indicator) <b>Green</b>	Off: the device is power off or failed		
		On: the device power on is normal		
	S(System indicator) <b>Red</b>	Off: the chip is normal		
		On: the chip read/write is unnormal		
	1-4(Copper ports)	<b>Green</b> indicators	<b>Yellow</b> indicators	
		Off: ports link down	Off: port speed is 10M	
		On: ports link up	On: port speed is 100M	
		Blinking: data on TX/RX		
5-6 ( Fiber ports) <b>Green</b>	Off: ports link down			
	On: ports link up			
	Blinking: data on TX/RX			
<b>Power parameters</b>				
Input voltage	12-58VDC, redundant power input			
Input current	0.5A Max			
Total power consumption	Full loading ≤5W			
Connector	Removable 4-pin terminal block			
Reverse polarity protection	Support			
Over-voltage protection	Support			
<b>Switching features</b>				
Switching capacity	1.2G			
Packet forwarding rate	0.892Mpps			

MAC address table	2K
VLAN	2K
Buffer	2Kbits
Forwarding delay	<100us
Jumbo Frame	Support 9Kbytes
MDX/MIDX	Support
Watchdog	Support
<b>Network Topology</b>	
Star topology	Support
Bus topology	Support
Tree Topology	Support
<b>Mechanical structure</b>	
Case protection	IP40
Installation method	Din-rail
Dimension(W*D*H)m m	30*98*98mm
Weight	0.6 kg
<b>Operating environment</b>	
Operating temperature	-40°C~+75°C
Storage/transportation temperature	-40°C~+85°C
Relative humidity	5%~95% (non-condensing)
<b>Industrial Standard</b>	Surge protection of power: IEC 61000-4-5 Level 3 (4KV/2KV) (8/20us)
	Surge protection of Ethernet ports: IEC 61000-4-5 Level 3 (4KV/2KV) (10/700us)
	DIP: IEC 61000-4-11 Level 3 (10V)
	ESD: IEC 61000-4-2 Level 4 (8K/15K)
	Shock: IEC 60068-2-27
	Free fall: IEC 60068-2-32
	Vibration: IEC 60068-2-6
<b>Certification</b>	CE/FCC/RoHS
<b>Warranty</b>	5 years