

Model No.	DK3110I-8T1S		
Interface	Fiber port	Copper RJ45 ports	
	1	8	
Ethernet	8*10/100/1000Base-T RJ45 1*1000Base-X SFP (SC/ST/FC optional)		
Standard	IEEE 802.3 10Base-T Ethernet IEEE 802.3u Fast Ethernet IEEE 802.3ab Gigabit Ethernet IEEE 802.3x Full-Duplex Flow Control IEEE 802.3az Energy Efficient Ethernet		
Dip Switch	1. Port Isolation 2. Flow control 3. QoS(1-2 ports) 4. Broadcast storm restrain		
LED Indicators	P(Power indicator) Green	Off: the device is power off or failed	
		On: the device power on is normal	
	S(System indicator) Red	Off: the chip is normal	
		On: the chip read/write is unnormal	
	1-8 (Copper ports)	Green indicators	Yellow indicators
		Off: ports link down	Off: port speed is 10/100M
		On: ports link up	On: port speed is 1000M
		Blinking: data on TX/RX	
	9 (Fiber port) Green	Off: ports link down	
		On: ports link up	
		Blinking: data on TX/RX	
Power parameters			
Input voltage	12-58VDC, redundant power input		
Input current	0.5A Max		
Total power consumption	Full loading ≤6.5W		
Connector	Removable 4-pin terminal block		
Reverse polarity protection	Support		
Over-voltage protection	Support		
Switching features			
Switching capacity	18G		

Packet forwarding rate	13.392Mpps
MAC address table	16K
VLAN	4K
Buffer	2M
Forwarding delay	<5us
Jumbo Frame	Support 10Kbytes
MDX/MIDX	Support
Watchdog	Support
Network Topology	
Star topology	Support
Bus topology	Support
Tree Topology	Support
Mechanical structure	
Case protection	IP40
Installation method	Din-rail
Dimension(W*D*H)m m	48*98*130mm
Weight	0.68kg
Operating environment	
Operating temperature	-40°C~+75°C
Storage/transportation temperature	-40°C~+85°C
Relative humidity	5%~95% (non-condensing)
Industrial Standard	Surge protection of power: IEC 61000-4-5 Level 3 (4KV/2KV) (8/20us)
	Surge protection of Ethernet ports: IEC 61000-4-5 Level 3 (4KV/2KV) (10/700us)
	DIP: IEC 61000-4-11 Level 3 (10V)
	ESD: IEC 61000-4-2 Level 4 (8K/15K)
	Shock: IEC 60068-2-27
	Free fall: IEC 60068-2-32
	Vibration: IEC 60068-2-6
Certification	CE/FCC/RoHS
Warranty	5 years

