



IDP150



► Features

- 15" 1024x768 LCD Touch Panel
- Projected Capacitive Multi-touch
- 1 VGA



► Panel



Back View



Bottom View

► Dimensions

Coming Soon

IDP150

► Specifications

DISPLAY

- 15" 1024x768 LCD monitor
- Supports projected capacitive multi-touch (10 points)
- Brightness: 350 nits
- Active area: 304.128mm x 228.096mm (H x V)
- Contrast ratio: 700:1
- Response time: 8ms
- View angle: 85°/85°/80°/80° (L/R/U/D)
- 30,000 MTBF LED backlight

I/O PORTS

- Bottom
 - 1 USB port (touch to external PC)
 - 1 VGA port
 - 1 audio-out port
 - 1 power connector

POWER

- Power input voltage: 100V~240V, 50Hz/60 Hz, 12V/3A

OS SUPPORT

- Windows 7
- Windows 8
- Windows 8.1
- Linux
- Android

ENVIRONMENT

- Temperature
 - Operating: 0°C ~ 40°C
 - Storage: -20°C ~ 60°C
- Humidity
 - Operating: 20% ~ 80% RH (non-condensing)
 - Storage: 10% ~ 90% RH (non-condensing)

VIBRATION

- TBD

SHOCK

- TBD

CONSTRUCTION

- Plastic

DIMENSIONS

- 340.37mm x 267.86mm x 44.3mm (W x H x D) (without stand)

WEIGHT

- 3.485kg

► Ordering Information

Model Name	P/N	Configuration	Remark
IDP150	790-IDP150-000G	15" Projected Capacitive Multi-touch Screen Monitor	MOQ : 100pcs

► Packing List

• 1 IDP150 Monitor
• 1 Power Cord
• 1 VGA Cable
• 1 USB Cable
• 1 Quick Guide