

VIO-117

17" SXGA Resistive / Capacitive Touch Display Module with 2x 10W Speaker

FEATURES

- 17" TFT XGA 4:3 LCD with Resistive 5-wire / Capacitive Touch
- -10°C to 60°C extended operating temperature
- Designed with Aluminum Die-Casting Front Frame
- IP65 Compliant Front Panel
- Two 10W Internal Speakers Built-in
- Multi-language OSD built-in

SPECIFICATIONS

DISPLAY

LCD Size	17" (4:3)
Max. Resolution	1280 x 1024 (SXGA)
Brightness (cd/m ²)	350
Contrast Ratio	800:1
LCD Color	16.7M
Pixel Pitch (mm)	0.264 (H) x 0.264 (V)
Viewing Angle (H-V)	170 / 160
Backlight MTBF	50000 hrs (LED Backlight)

TOUCH

Resistive 5-wire	VIO-117R Only
Projected Capacitive	VIO-117C Only

I/O

Internal Speaker	AMP 10W + 10W
------------------	---------------



OSD	LCD On/Off, Auto, Menu, Up and Down Multi-language
-----	---


ENVIRONMENT

Operating Temp.	-10°C to 60°C
Storage Temp.	-20°C to 70°C
Relative Humidity	10%~80% (non-condensing)
IP Level	IP 65 Compliant Front Panel

PHYSICAL

Front Panel Construction	Die-cast Flat Surface
Dimension	431.5 (W) x 344 (D) x 34.5 (H)mm
Weight	VIO-117R: 5.20kg VIO-117C: 5.11kg
Mounting	VESA Mounting Holes 75 x 75mm, 100 x 100mm

DIMENSION



AVAILABLE MODELS

MODEL NO.	DESCRIPTION
VIO-117R	17" SXGA Resistive Touch Display Module with 2x 10W Speaker
VIO-117C	17" SXGA Capacitive Touch Display Module with 2x 10W Speaker

PACKING LIST

- 1x VIO-117 Series Display Module
- 10x Panel Mount Kit