



# Handheld Fanless Panel PC

10.1"

13.3"



The back panel I/O is flexible for customized configuration.



Model Name		10.1"+2I268HB	13.3"+2I268HB
Dimension (mm)		250W x 40H x 168D mm	349.2W x 40H x 220.8D mm
Weight		2.6 Kg	3 Kg
Hard drive		2.5" HDD Share with battery	2.5" HDD Share with battery
LCD brand		CPT	CHIMEI
LCD size		10.1 inch, 16:9	13.3 inch, 16:9
Max Resolution		1280 x 800	WSVGA 1366 x 768
Luminance (cd/m2)		500	200
Contrast Ratio		500:1	500:1
Viewing Angle (H-V)		140(H)-120(V)	45/45/20/45 CR≥10 (L/R/U/D)
Backlight		LED	LED
Touch Screen		Resistive touch screen	Resistive touch screen
MB		2I268HB	2I268HB
CPU		Intel Cedarview-M N2600 1.6 GHz Intel Cedarview-M N2800 1.86 GHz	Intel Cedarview-M N2600 1.6 GHz Intel Cedarview-M N2800 1.86 GHz
Chipset		Intel Cedarview-M + NM10	Intel Cedarview-M + NM 10
Memory	Type / Capacity	DDR3 800 MT/s for N2600,Max up to 2GB DDR3 1066 MT/s for N2800,Max up to 4GB	DDR3 800 MT/s for N2600,Max up to 2GB DDR3 1066 MT/s for N2800,Max up to 4GB
	SO-DIMM	N/A	N/A
On board memory		2GB	2GB
SSD Storage	CF (CFast)	N/A	N/A
	mSATA	Yes	Yes
	On Board SSD	Optional	Optional
VGA		Optional	Optional
DVI / HDMI		Optional	Optional
USB		4	4
COM		Built-in 1 x COM, expand up to 2 x COM	Built-in 1 x COM, expand up to 2 x COM
Mini-PCle		2	2
SIM Card Holder		1 (optional)	1 (optional)
GPIO		4DI / 4DO (Optional)	4DI / 4DO (Optional)
Ethernet		Realtek GbE x 1	Realtek GbE x 1
Audio		Line-in / Line-out	Line-in / Line-out
Power Input		DC IN +12V with Li Battery charger function	DC IN +12V with Li Battery charger function
Battery		Support battery pack 7.4V~8.4V, 3500~10500 mAh	Support battery pack 7.4V~8.4V, 3500~10500 mAh
Mounting		VESA 75/100	VESA 75/100
Panel frame water proof		IP65	IP65
Expansion		Rechargeable Battery Pack, GPS, 3G/4G, Bluetooth, WI-FI, I/O	Rechargeable Battery Pack, GPS, 3G/4G, Bluetooth, WI-FI, I/O
Operating Temp.		0°C~50°C for HDD, 0°C~60°C for mSATA	0°C~50°C for HDD, 0°C~60°C for mSATA
Operating Humidity		5~90% @ 39°C, non-condensing	5~90% @ 39°C, non-condensing