

2017

# Mainboard

## Product Launch Guide

--[**IMB-1900-6C**]

NC Series Motherboard



Jetway Information Co., Ltd.

[www.jetway.com.tw](http://www.jetway.com.tw)

Date : April ,7, 2017





1. Intel® Celeron™ J1900 (2.0 GHz) quad-core processor
2. Support DirectX 11 3D Graphics Acceleration
3. Support DDR3L 1333
4. Integrated HD Audio CODEC
5. Support 1\*PCI Express Gigabit LAN
6. Support Power Onboard(12V)
7. Onboard 1\*MiniPCI-E connector
8. Onboard 1 \*M.2 connector(2242/2260)
9. 2 Phase CPU Power Support
10. Support 1\*USB3.0 and 9\*USB2.0
11. Support 6\*COM
12. Support Amplifier function(3W)
13. Support Thunder Protection Function
14. Thin mini ITX Form Factor(170mm X170mm)

**Mainboard Specifications**

■ <b>CPU-Chipset</b>	<ul style="list-style-type: none"> <li>■ INTEL® Celeron™ J1900 (2.0 GHz) quad-core processor</li> <li>■ 2 Phase CPU Power Support</li> </ul>
■ <b>I.O Chipset</b>	<ul style="list-style-type: none"> <li>■ FINTEK F81866AD-I</li> </ul>
■ <b>Memory</b>	<ul style="list-style-type: none"> <li>■ 1*SO-DIMM slot</li> <li>■ Support DDR3L 1333</li> <li>■ Max. capacity of system memory up to 8GB</li> </ul>
■ <b>Expansion Slots</b>	<ul style="list-style-type: none"> <li>■ 1* Mini PCI-E connector</li> </ul>
■ <b>Storage</b>	<ul style="list-style-type: none"> <li>■ 1* Serial ATA2 3Gb/s connector</li> <li>■ 1* M.2 Connector(2242/2260)</li> </ul>
■ <b>Audio</b>	<ul style="list-style-type: none"> <li>■ ALC662 Audio CODEC</li> <li>■ HD Audio CODEC</li> </ul>
■ <b>Ethernet LAN</b>	<ul style="list-style-type: none"> <li>■ REALTEK® RTL8111G Chip</li> <li>■ 1* PCI Express Gigabit LAN</li> </ul>
■ <b>EDP</b>	<ul style="list-style-type: none"> <li>■ 1*EDP</li> </ul>
■ <b>USB</b>	<ul style="list-style-type: none"> <li>■ 1*USB3.0 Port</li> <li>■ 9* USB 2.0(5 distribute in back panel, 4 distribute in mid-board)</li> </ul>
■ <b>Special Features</b>	<ul style="list-style-type: none"> <li>■ Support CPU Smart Fan</li> <li>■ Support Watch dog Technology</li> <li>■ Support VGA header</li> <li>■ Support HDIM header</li> <li>■ Support Power On board</li> <li>■ Support Amplifier function(3W)</li> </ul>

	<ul style="list-style-type: none"> <li>■ COM1/COM2 Support TTL</li> <li>■ Thunder Protection Function</li> <li>■ All Solid Capacitor design</li> <li>■ All Power Pack MOSFET design</li> </ul>
■ <b>Back Panel I / O</b>	<ul style="list-style-type: none"> <li>■ 1* USB3.0 port</li> <li>■ 5* USB2.0 ports</li> <li>■ 1* RJ-45 port</li> <li>■ 1* Line-out connector</li> <li>■ 1* MIC</li> <li>■ 1* VGA port</li> <li>■ 1* 12V DC in</li> </ul>
■ <b>Internal I / O</b>	<ul style="list-style-type: none"> <li>■ 2* USB 2.0 headers for 4 USB 2.0 ports</li> <li>■ 1* CPU / Chassis Fan connectors</li> <li>■ 6* COM headers</li> <li>■ 1* Parallel header</li> <li>■ 1* PS2/KB header</li> <li>■ 1* 4-pin ATX 12V Power connector</li> <li>■ 1* 4-pin SATA Power connector</li> <li>■ 1* 15-pin VGA header</li> <li>■ 1* 20-pin HDMI header</li> <li>■ 1* EDP header</li> <li>■ 1* Mini PCI-e connector</li> <li>■ 1* M.2 Connector(2242/2260)</li> <li>■ 1* SATA Connector</li> <li>■ 1* Speaker header(Amplifier function 3W)</li> <li>■ 1* Front panel header</li> <li>■ 1* SIM Card socket</li> </ul>
■ <b>BIOS</b>	<ul style="list-style-type: none"> <li>■ AMI 64MB SPI ROM</li> </ul>
■ <b>Temperature</b>	<ul style="list-style-type: none"> <li>■ Operating: 0°C ~ 60°C</li> <li>■ Storage: -20°C ~ 85°C</li> </ul>
■ <b>Form Factor</b>	<ul style="list-style-type: none"> <li>■ Thin mini ITX Form Factor(170mm X 170mm)</li> </ul>