

ST935K Android 7.0 10 inch rugged tablet with fingerprint

10.1 inch, Android 7.0 OS/Windows 10 pro, Quad core, 1.8GHz CPU,NFC,Rugged Tablet PC with 4G LTE

Optional functions: 2D bar code scanner, Fingerprint,docking station

SPECIFICATIONS

Standard function	
Operating System	Android 7.0
CPU	MT6735
GPU	Qualcomm® Adreno™ 506 GPU,650Mhz
RAM	RAM: 3GB
	FLASH: 32GB
Extended Storage	Micro SD, Maximum 128G
USB port	5 pin MicroUSB; Support to connect U-disk/Mouse/Keyboard/OTG line,RJ45,normal USB,back popopin,Mini HDMI,RS232
OTG	Through OTG can meet 100M network port, network card setup, PPPoE dial-up, web browsing. Support OTG extend RS232 serial port/485 serial port/RJ45 Serial port
External port	Charge port, headphone port
Protection Grade	
Industrial Protection Grade	IP65
Drop Grade	Drop resistance from 1.2m
Wireless Communication	
Bluetooth	Support 4.1
GPS	GPS+BDS+GLONASS
WIFI	Support IEEE 802.11a/b/g/n/ac (2.4G and 5G bands)
2G/3G/4G LTE	4G Fre: FDD: B1,B2, B3,B5, B7, B8, B12, B20 TDD: B38,B39,B40,B41 B34 WCDMA:B1, B8 TD-SCDMA: B34, B39 GSM/GPRS/EDGE
Physical Parameters	
Display Screen	10 inch LCD screen, 1920*1200 IPS screen, capacitive touch screen
Keyboard	Android menu, Homepage, Return, Volume, Barcode, ON/OFF, Reset
Camera	5 million pixels front camera, 13 million pixels rear camera with automatic focus and lighting function
Headset	3.5mm audio Interface, has MIC and Single loudspeaker
LED indicator light	Support (ordinary flicker, Call fast flicker, missed calls, charge indicator)

Flashlight Function	Support, can be used for emergency lighting
Googleplay store	Support
Gravity Sensor	Support
Compass	Support
Acceleration sensors	Support
Magnetometer	Support
Light and distance sensor	Support
Vibrating motor	Support
FM	Support
Rechargeable Lithium Battery	5V, 10500mAh
Standby	About 500 hours
Working time	About 8 hours
Dimension	275*178*18mm
Weight	810g
Environmental Characteristics	
Working Temperature	-20℃ ~ +60℃
Storage Temperature	-25℃ ~ +80℃
Humidity	5%-95% relative humidity; no condensation
Optional function	
Barcode Scanning	2D Barcode Scanner Index(Internal): Honeywell N3680 Motorola SE4750 Identification ability: 1D, 2D, OCR Scanning angle: rotate 360°, incline±50°, deflection ±50° Field of View: Horizontal 36°, vertical 23° Depth of field: 4cm-23.5cm Environmental luminance: 0~100,000 LUX
RFID	HF RFID(Internal): Support NFC/NXP, 13.56MHZ ISO14443A,B and ISO15693 protocol, reading distance 0-3cm, Tag support type:SR176,SRIX4K(TYPE-B),I-Code2,TI RFID Tag-it HF-I,EM4034,Mifare Classic ETC