


Apacer

The Most **Reliable**
Storage For Industries




UDM 1U



Overview

UDM 1U is small form factor that electrically complies with High-speed USB 3.0 interface. Tailored for the 1U server, the new series boasts upgraded speeds and a doubling of capacity. The minimum height is only 22.4mm, enhancing the air ventilation inside the 1U chassis. The actual available memory on the device is less than what is listed on the package. This is due to small discrepancies in file formats and algorithms used by various operating systems. In addition, a portion of memory space is reserved for system files and data sectors for better performance.




Feature

- Compliant with the standard USB
- 20-pin Connector, Pin-Pitch B
- High-speed transmission
- Built-in S.M.A.R.T. Function
- Hardware Write Protect (Optional)

Specifications

Model	UDM 1U
Interface	USB 3.0
Connector	20-pin (2x10) female header
NAND Flash Type	SLC
Capacity	128MB~16GB
External DRAM	No
Sustained Read Performance (MB/sec)	Up to 41
Sustained Write Performance (MB/sec)	Up to 36
ECC Engine	Built-in up to 72-bit per 1K bytes BCH ECC
Standard Operating Temperature (°C)	0 ~ + 70
Extended Operating Temperature (°C)	-40 ~ + 85
Storage Temperature (°C)	-40 ~ + 100
Shock	Operation: 50G, 11ms Non-operation: 1500G, 0.5ms
Vibration	Operation: 7.69 Grms, 20~2000 Hz/random (compliant with MIL-STD-810G) Non-operation: 15G, 10 ~ 2000 Hz/sine
Operating Voltage	3.3 V ± 5%
Power Consumption	Active mode: 150 mA & Idle mode: 70mA
Dimension (L x W x H)	20 x 22.4 x 1 (mm)
MTBF (hours)	>1,000,000

Mechanical Specification



Unit: mm

For more information, contact your Apacer representative

Global Presence

Taiwan (Headquarters)
Apacer Technology Inc.
Tel: +886-2-2267-8000
Fax: +886-2-2267-2261

Europe
Apacer Technology B.V.
Tel: +31-40-267-0000
Fax: +31-40-290-0686

U.S.A.
Apacer Memory America, Inc.
Tel: +1-408-518-8699
Fax: 1-510-249-9551

China
Apacer Electronic(Shanghai)
Co., Ltd.
Tel: +86-21-6228-9939

Japan
Apacer Technology Corp.
Tel: +81-3-5419-2668
Fax: +81-3-5419-0018

India
Apacer Technologies Pvt. Ltd.
Tel: +91-80-41529061~3
Fax: +91-80-41700215